

CFW500 - VARIABLE SPEED DRIVE

High performance and reliability to improve your production process



CFW500

Variable Speed Drive

Summary

Introduction	04
Simplified Programming and Operation	06
Flexibility and Performance	07
Connectivity	08
Features	09
Embedded Safety Functions	10
Pump Genius	11
Applications	12
Coding	13
Specification	14
Accessories	19
Dimensions and Weights	21
Standards	22
Technical Specifications	23
Block Diagram of IP20 / NEMA Type 1 Version	24
Block Diagram of IP66 / NEMA Type 4x Version	25



CFW500

Machinery Drive

Endless possibilities

With modern design, the variable speed drive CFW500 is a **high performance** VSD for applications that require speed and torque control of three-phase induction motors. The equipment has **sensorless vector control, closed loop vector control or scalar V/f**. It also has SoftPLC, which adds PLC (programmable logic controller) functions, safety functions (STO and SS1) - making easier to comply the machine and application safety requirements, Pump Genius, which adds dedicated functions for pumping systems and selectable plug-in modules, that **provide a flexible and optimized solution** for any application.



High performance

Optional version with integrated safety functions

Wide power range and high overload capacity

High performance control methods



Flexible

Connectivity

Advanced resources and functions

Assembly options



Robust

Version with IP66 / NEMA type 4x



Innovative

SoftPLC - built-in PLC functionalities

Free programming softwares



Reliable

WEG Quality

Protection against ground fault, short circuit, over temperature and others

Internal RFI filter to reduce high-frequency electromagnetic interference



Integrated STO (Safe Torque Off) and SS1 (Safe Stop 1) fulfills requirements for safety performance SIL 3 / PL e, according to IEC 61800-5-2, EN ISO 13849-1, EN 62061, IEC 61508 and IEC 60204-1

Provides machine builders a cost-effective solution to design protective measures to reduce the risk from unexpected and hazardous movement in industrial machines

Models from 1,0 to 105 A (0,25 kW / 0,33 HP to 55 kW / 75 HP) at supply voltages 200-240, 380-480 or 500-600 V

Permits the CFW500 to be used in a large variety of applications, improving their overall performance

Sensorless or closed loop vector control, VVW or Scalar V/f and permanent magnet motor control: VVW PM

USB and fieldbus communication modules for the most used industrial networks, like CANopen, DeviceNet, Profibus-DP, EtherNet/IP, PROFINET IO or Modbus-RTU

Full integration with process network

Pump Genius software

Dedicated functions ideal for pumping systems

Surface or DIN rail mounting, including side-by-side installation

Saves space and cabling, reducing installation costs

Complete protection against contact with internal live parts, avoiding the entrance of dust or water coming from jets

The high protection degree dispenses the panel, reducing installation costs

The VSD, motor and application can work in an interactive way, because it is possible to make customized logic and applications.

Ideal for machinery manufacturer

WLP, WPS and SuperDrive G2 softwares available at www.weg.net

100% of the VSDs are tested at the factory under full load and maximum temperature

High reliability

Conformal Coating (Tropicalization) as standard, class 3C2 according to IEC 60721-3-3 and 3C3 as an option, to protect against corrosive gases in harsh environments

VSD lifetime is extended

It prevents damage to the inverter which can be caused by adverse situations, normally external factors.


Certifications



Simplified Programming and Operation

Operating Interface (HMI)

- Monitoring, setting of all parameters as well as commands
- Up to three parameters indication on the display, according to user selection
- Oriented start-up and grouped parameters



Note: the operating interface (HMI) of the CFW500 is not removable. For remote operation of the HMI, use the CFW500-HMIR accessory, according to the accessory table on page 19.

Remote Operating Interface (HMI)


Solutions for machine consoles and panels.



Flexibility and Performance

The CFW500 has a modern design and it can be selected according to the application requirements, providing flexibility with excellent performance. The VSD gives the user the possibility to choose the plug-in module that best fits his application, or to use the standard version, that comes with the CFW500-IOS plug-in module. All plug-in modules comes with one RS485 port as standard.

The installation of the CFW500 is simple and its configuration and operation is intuitive with the navigation menus of the operating interface (HMI) with built-in LCD display. By using the flash memory module, it is possible to download the existing setting from one CFW500 to other units without powering them up.



Conformal Coating
Improved 3C2 class of coating on the internal circuits of all versions and extra 3C3 Class coating (optional) according to IEC 60721-3-3 ensures improved protection in environments with corrosive chemicals.


Flash Memory Module (CFW500-MMF Accessory)
Download/Upload the settings to other CFW500 units without the need to power them up.

Plug-In Modules
Selectable according to the application.

Easily Removable Fan
The quick change system ensures simple and fast fan maintenance.

SoftPLC
It is a software resource added to the CFW500 which allows the user to implement and debug logic projects equivalent to a small PLC (Programmable Logic Controller), customizing and integrating the CFW500 to the application. The free WPS programming software is available at: www.weg.net.

Connectivity



The CFW500 can be connected to the main fast industrial Fieldbus communication networks, with protocols used worldwide such as CANopen, Profibus-DP, DeviceNet, PROFINET IO, EtherNet/IP and Modbus-TCP, according to the plug-in module selected.

In addition, all plug-in modules come with serial interface RS485 Modbus-RTU built-in.

- I/O expansion:
IOS (standard, included in the version with plug-in), IOD, IOAD, IOR
- Functionality expansion:
Incremental encoder
USB
- Fieldbus communication protocols:
CANopen
DeviceNet
RS232
RS485
Profibus-DP
EtherNet/IP
Modbus-TCP
PROFINET IO

Selectable plug-in modules


Remote operating interface (HMI) (CFW500-HMIR accessory)

Easy operation and view

Free at www.weg.net


SuperDrive G2

USB Connection (CFW500-CUSB accessory)



Features

- Special engineering units (RPM, °C, Nm, mA, %, kW, kWh, among others)
- Password to protect the parameters
- Backup of all parameters (via SuperDrive G2 software, or plugin memory MMF)
- Possibility to save up to two different settings on the memory of the CFW500
- Setting of the switching frequency according to the application requirements
- Speed reference via electronic potentiometer
- Multispeed with up to eight programmable speeds
- Slip compensation
- Manual or automatic torque boost (V/F scalar mode) or self-adjustment (VVW and vector modes)
- Permanent magnet motor control: VVW PM
- Acceleration/deceleration ramps
- "S" type ramp
- DC braking
- Internal dynamic braking (except frame size A)
- PID controller to control processes in closed loop
- Flying start / Ride-through
- Sleep mode
- Skip frequencies or frequency ranges function adjustable
- Overload and overtemperature protection
- Overcurrent protection
- DC link voltage supervision
- Fault log
- Safety functions: STO and SS1



Using the SuperDrive G2 software, it is possible to change, monitor and view graphically the variables of the CFW500 on a personal computer.

Trend Function

Trend charts for online monitoring of parameters and other variables within the SuperDrive G2 software.

Embedded Safety Functions¹⁾

Used to reduce risk and to guarantee the safety of personnel and environment if there is a hazardous event due to a fault in operating machines. The embedded safety functions **STO and SS1** provide machine builders a cost-effective solution to design protective measures and reduce the risk from unexpected and hazardous movement in industrial machines and processes.

Advantages

- Safety functions integrated in the CFW500 drive, making easier to comply with the machine and application safety requirements
- Less components, no need for additional wiring, saving space and installation costs
- Easier installation, commissioning and maintenance
- No electromechanical components, meaning faster responses and higher degree of productivity
- Due to the high safety performance level SIL3, the CFW500 with Safety module may avoid the use of external safety relays for cables and emergency pushbuttons monitoring




Safety Functions

STO (Safe Torque Off)

This function immediately switches off the drive output to the motor, disabling the supply of torque-generating energy. STO is also used to prevent an unexpected startup of machinery or for an emergency stop, fulfilling stop category 0 (IEC 60204-1).

It is applicable if the motor can be brought to a standstill in a sufficiently short time by the load torque or friction or where motor coast to a stop is not relevant to safety.



SS1 (Safe Stop 1)

This function enables motor deceleration and then, after a delay time, activates the STO function. SS1 can be used to implement a controlled stop and then removal of power, fulfilling stop category 1 according to IEC 60204-1. This function is used when, in the event of a safety related fault, the drive must stop as quickly as possible and then enter the STO state.

The stopping of a drive by means of SS1 function reduces the risk of danger, eliminates the need of external safety timers, increases the productivity of a machine and allows safety clearances in a machine to be reduced. The reason is the active stopping of the drive as compared with the use of the STO function only.



Note: 1) Safety Functions STO and SS1 are available in CFW500...Y2 version. It fulfils requirements for safety performance SIL 3 / PL e, according to IEC 61800-5-2, EN ISO 13849-1, EN 62061, IEC 61508 and IEC 60204-1.

Pump Genius

The Pump Genius is a customizable feature of WEG drives that enables your standard CFW500 to become dedicated for pumping systems. It ensures accurate pressure / flow control throughout the processing cycle, starting with raw water and its usage, ending on wastewater treatment. With an easy-to-use programming wizard, Pump Genius helps you to minimize downtime and maximize energy savings. Everything you need is selecting one option that best fits your application:

simplex


The Pump Genius Simplex software adds ideal features to the VSD for single pump control.

multipump

Pump Genius Multipump allows driving two or more pumps with only one inverter.

multiplex¹⁾


Pump Genius Multiplex permits the VSDs to control, monitor and manage the entire system on their own, eliminating the need of external PLC.



Energy Savings


The use of the CFW500 with the Pump Genius Multipump improves the performance and provides electric energy savings.

Using this solution together with WEG W22 Premium motors, and reducing the pump speed even if slightly, it is possible to reduce the electric energy consumption by approximately 15%, thus contributing to the sustainable development of the planet.




Broken Pipe Alarm

Pump Genius detects when the pump is consuming more electric energy than it should, by means of information on the pump load and speed, automatically generating an alarm warning of leaky pipes. In addition, with the monitoring of the system pressure, a clogging condition may be detected by configuring the maximum pressure to trigger the alarm of clogged pipe.



Sleep and Wake up Function

The sleep function keeps the pump in the standby mode when the demand or flow is below the minimum, avoiding that it runs at low speed for long periods, providing electric energy savings and increasing the lifetime of the pump. The wake up function restarts the drive automatically when the pressure falls below the set point.



Pipe Charging Function

It allows lubrication and smooth initial charging of the pipes, making the pump operate at a lower preset speed for a certain time, avoiding "Water Hammers", which may damage the piping system.

Note: 1) Under development.
Find out more about Pump Genius visiting our website www.weg.net.

Applications

Extruders



Conveyor belts



Roller tables



Fans / exhausters




Centrifugal pumps



Granulators / palletizers



Cutting and welding machines



Dryers and rotary ovens



Process dosing pumps



Stirrers / mixers



Rotary filters



Winding machines /
uncoiling machines



Coding¹⁾

- 1
- CFW500
- 2
- A
- 3
- 02P6
- 4
- T
- 5
- 4
- 6
- NB
- 7
- 20
- 8
- C2
- 9
- Y2
- 10
-
- 11
-

- 1 - CFW500 variable speed drive
- 2 - Size of the CFW500, according to table 1 below
- 3 - Rated output current, according to table 1 below

Power supply	Single-phase (S)	Single-phase or three-phase (B)	Three-phase (T)		
Voltage	200-240 V ac	200-240 V ac	200-240 V ac	380-480 V ac	500 - 600 V ac
Current	01P6 = 1.6 A 02P6 = 2.6 A 04P3 = 4.3 A 07P0 = 7.0 A 07P3 = 7.3 A 10P0 = 10 A	01P6 = 1.6 A 02P6 = 2.6 A 04P3 = 4.3 A 07P3 = 7.3 A 10P0 = 10 A	07P0 = 7.0 A 09P6 = 9.6 A 16P0 = 16 A 24P0 = 24 A 28P0 = 28 A 33P0 = 33 A 47P0 = 47 A 56P0 = 56 A	01P0 = 1.0 A 01P6 = 1.6 A 02P6 = 2.6 A 04P3 = 4.3 A 06P1 = 6.1 A 02P6 = 2.6 A 04P3 = 4.3 A 06P5 = 6.5 A 10P0 = 10 A 14P0 = 14 A 16P0 = 16 A 24P0 = 24 A 31P0 = 31 A 39P0 = 39 A 49P0 = 49 A 77P0 = 77 A 88P0 = 88 A 0105 = 105 A	01P7 = 1.7 A 03P0 = 3.0 A 04.3 = 4.3 A 07P0 = 7.0 A 10P0 = 10 A 12P0 = 12 A

4 - Number of phases

S	Single-phase power supply
B	Single or three-phase power supply
T	Three-phase power supply

5 - Rated voltage

2	200-240 V
4	380-480 V
5	500-600 V

6 - Internal dynamic braking²⁾

NB	Without internal dynamic braking IGBT
DB	With internal dynamic braking IGBT

7- Protection degree

20	IP20 protection degree
N1	Cabinet type 1 protection degree
66	IP66 protection degree (Type 4x)

8 - RFI filter³⁾

Blank	Without internal RFI filter
C2	With internal RFI filter - category 2
C3	With internal RFI filter - category 3

9 - Disconnect switch⁴⁾

Blank	Without disconnect switch
DS	With disconnect switch

10 - Safety function⁵⁾

Blank	Without safety function
Y2	With safety function (STO and SS1-b) as per EN 61800

11 - Special hardware versions - H xx

11.1 - Plug-in module

Blank	With standard plug-in module
H00	Without plug-in module

11.2 - Coating for harsh environments

Blank	Class 3C2 - Standard conformal coating
EC	Class 3C3 - Extra coating

12 - Special software version - S xx

Blank	Standard software
Sxx	Special software

Notes: 1) Other configurations available upon request.

2) Braking resistor not included. Braking IGBT is available as standard for the whole CFW500 line, except for frame size A of IP20 version.

3) Conducted emission level (IEC 61800-3).

In order to minimize such problem, WEG variable speed drives contain common-mode capacitive filters, which are enough to avoid this type of interference in most cases. If necessary, our inverters also have radio frequency (RF) filters to reduce even more those high-frequency electromagnetic interference signals. Item 8 of the table above shows how to select the models of internal RFI filters for the CFW500.

Definitions of IEC/EN 61800-3 standard. Categories:

Category C1: variable speed drives with voltage rating below 1,000 V and intended for application in the "First Environment".

Category C2: inverters with voltage rating below 1,000 V not provided with plugs or movable installations, and, when applied in the "First Environment", they must be installed and commissioned by a professional.

Category C3: inverters with voltage ratings below 1,000 V developed for application in the "Second Environment" and not designed for application in the "First Environment".

Environments: First Environment: environments that include domestic installations, such as establishments directly connected without intermediate transformers to the low voltage power line, which supplies buildings used for domestic purposes.

Second environment: environments that include all the buildings other than those directly connected to the low voltage power line, which supplies buildings used for domestic purposes.

4) Only for IP66 version.

5) Only for frames A to E of IP20 version and rated voltages 200-240 V or 380-480 V.

Specification

CFW500 IP20 or NEMA Type 1 - 200-240 V

CFW500 variable speed drive											Maximum applicable motor ¹⁾						
Reference ²⁾								Power supply (V)		Frame size	Rated current (A) ²⁾	IEC				UL	
												60 Hz		50 Hz		60 Hz	
Coding (available options for each model)											220-230 V ac		220-230 V ac		230 V ac		
1, 2, 3, 4, 5 and 6	7	8	9	10	11.1	11.2	12				HP	kW	HP	kW	HP		
CFW500A01P6S2NB	20 or N1	Blank or C2	Blank	Blank or Y2 ³⁾	Blank or H00	Blank or EC	Blank or Sxx	Single-phase	200-240	A	1.6	0.25	0.18	0.33	0.25	0.33	
CFW500A02P6S2NB		Blank or C2									2.6	0.5	0.37	0.75	0.55	0.75	
CFW500A04P3S2NB		Blank or C2									4.3	1.0	0.75	1.5	1.1	1.5	
CFW500A07P0S2NB		Blank or C3								7.0	2.0	1.5	2.0	1.5	2.0		
CFW500B07P3S2DB		C2								B	7.3	2.0	1.5	2.0	1.5	2.0	
CFW500B10P0S2DB		C2									10	3.0	2.2	3.0	2.2	3.0	
CFW500A01P6B2NB		Blank						Single-phase or three-phase	200-240	A	1.6	0.25	0.18	0.33	0.25	0.33	
CFW500A02P6B2NB		Blank									2.6	0.5	0.37	0.75	0.55	0.75	
CFW500A04P3B2NB		Blank									4.3	1.0	0.75	1.5	1.5	1.5	
CFW500B07P3B2DB		Blank								B	7.3	2.0	1.5	2.0	1.5	2.0	
CFW500B10P0B2DB		Blank									10	3.0	2.2	3.0	2.2	3.0	
CFW500A07P0T2NB		Blank								A	7.0	2.0	1.5	2.0	1.5	2.0	
CFW500A09P6T2NB		Blank									9.6	3.0	2.2	3.0	2.2	3.0	
CFW500B16P0T2DB		Blank									B	16	5.0	3.7	5.5	4.0	5.5
CFW500C24P0T2DB		Blank								C		24	7.5	5.5	7.5	5.5	7.5
CFW500D28P0T2DB		Blank or C3									D	28	10	7.5	10	7.5	10
CFW500D33P0T2DB		Blank or C3										33	12.5	9.2	12.5	9.2	12.5
CFW500D47P0T2DB		Blank or C3								47		15	11	15	11	15	
CFW500E56P0T2DB	Blank or C3	E	56	20	15	20	15	20									

Notes: 1) The power values for maximum applicable motor shown in the tables above are reference values and valid for WEG motors. IEC motor powers are based on motor WEG four-pole W22 High Efficiency IE2 three-phase induction motors with power supply of 220 V, 230 V, 380, 400 V, 525 or 575 V. NEMA motor power are based on WEG four pole W22 Premium. Motor rated currents may vary with speed and manufacturer, therefore, use the motor power ratings above only as a guidance. The proper sizing of the CFW500 to be used must be determined as a function of the rated current of the motor used.
 2) The rated current informed for models of frames A to E are for HD (heavy duty) operation and for models of frame F are for ND (normal duty) operation. For further information, please check the user's manual.
 3) The optional version with protection degree NEMA type 1 is not compatible with safety function.



Specification

CFW500 IP20 or NEMA Type 1 - 380-480 V

CFW500 variable speed drive								Maximum applicable motor ¹⁾										
Reference ²⁾								Power supply (V)		Frame size		Rated current (A) ²⁾		IEC				UL
														60 Hz		50 Hz		60 Hz
Coding (available options for each model)								380 V ac		380-400 V ac		400 V ac	440-460 V ac					
										HP	kW	HP	kW	HP				
1, 2, 3, 4, 5 and 6	7	8	9	10	11.1	11.2	12											
CFW500A01P0T4NB	20 or N1	Blank or C2	Blank	Blank or Y2 ³⁾	Blank or H00	Blank or EC	Blank or Sxx	Three-phase	380-480	A	1.0	0.25	0.18	0.5	0.37	0.5		
CFW500A01P6T4NB		1.6									0.5	0.37	0.75	0.55	0.75			
CFW500A02P6T4NB		2.6									1.5	1.1	1.5	1.1	1.5			
CFW500A04P3T4NB		4.3									2.0	1.5	2.0	1.5	3.0			
CFW500A06P1T4NB		6.1									3.0	2.2	4.0	3.0	4.0			
CFW500B02P6T4DB		B									2.6	1.5	1.1	1.5	1.1	1.5		
CFW500B04P3T4DB											4.3	2.0	1.5	2.0	1.5	2.0		
CFW500B06P5T4DB											6.5	3.0	2.2	4.0	3.0	5.0		
CFW500B10P0T4DB											10	5.0	3.7	5.5	4.0	7.5		
CFW500C14P0T4DB		C									14	7.5	5.5	7.5	5.5	10		
CFW500C16P0T4DB										16	10	7.5	10	7.5	10			
CFW500D24P0T4DB		D								24	15	11	15	11	15			
CFW500D31P0T4DB										31	20	15	20	15	25			
CFW500E39P0T4DB		E								39	25	19	25	19	30			
CFW500E49P0T4DB										49	30	22	30	22	40			
CFW500F77P0T4DB		F								77	50	37	50	37	60			
CFW500F88P0T4DB										88	60	45	60	45	75			
CFW500F105T4DB										105	75	55	75	55	75			

CFW500 IP20 or NEMA Type 1 - 500-600 V

CFW500 variable speed drive								Maximum applicable motor ¹⁾										
Reference ²⁾								Power supply (V)		Frame size		Rated current (A) ²⁾		IEC				UL
														60 Hz		50 Hz		50 Hz
Coding (available options for each model)								575 V ac		575 V ac		525 V ac	575 V ac					
										HP	kW	HP	kW	kW	HP			
1, 2, 3, 4, 5 and 6	7	8	9	10	11.1	11.2	12											
CFW500C01P7T5DB	20 or N1	Blank	Blank	Blank	Blank or H00	Blank or EC	Blank or Sxx	Three-phase	600	C	1.7	1.0	0.75	1.0	0.75	0.75	1.5	
CFW500C03P0T5DB											3.0	2.0	1.5	2.0	1.5	1.5	2.0	
CFW500C04P3T5DB											4.3	3.0	2.2	3.0	2.2	2.2	3.0	
CFW500C07P0T5DB											7.0	5.0	3.7	5.5	4.0	4.0	5.0	
CFW500C10P0T5DB											10.0	7.5	5.5	7.5	5.5	5.5	10	
CFW500C12P0T5DB											12.0	10	7.5	10	7.5	7.5	10	

Notes: 1) The power values for maximum applicable motor shown in the tables above are reference values and valid for WEG motors. IEC motor powers are based on motor WEG four-pole W22 High Efficiency IE2 three-phase induction motors with power supply of 220 V, 230 V, 380, 400 V, 525 or 575 V. NEMA motor power are based on WEG four pole W22 Premium. Motor rated currents may vary with speed and manufacturer, therefore, use the motor power ratings above only as a guidance. The proper sizing of the CFW500 to be used must be determined as a function of the rated current of the motor used.
 2) The rated current informed for models of frames A to E are for HD (heavy duty) operation and for models of frame F are for ND (normal duty) operation. For further information, please check the user's manual.
 3) The optional version with protection degree NEMA type 1 is not compatible with safety function.

Specification

CFW500 IP66 (NEMA Type 4x) - 200-240 V

CFW500 variable speed drive										Maximum applicable motor ¹⁾						
Reference ²⁾								Power supply (V)	Frame size	Rated current (A) ²⁾	IEC				UL	
											60 Hz		50 Hz		60 Hz	
Coding (available options for each model)								200-230 V ac	200-230 V ac	230 V ac						
1, 2, 3, 4, 5 and 6	7	8	9	10	11.1	11.2	12				HP	kW	HP	kW	HP	
CFW500A01P6S2DB	66	C3	Blank or DS	Blank	Blank or H00	Blank or EC	Blank or Sxx	Single-phase	200-240	A	1.6	0.25	0.18	0.33	0.25	0.33
CFW500A02P6S2DB		C3									2.6	0.5	0.37	0.75	0.55	0.75
CFW500A04P3S2DB		C3									4.3	1.0	0.75	1.5	1.1	1.5
CFW500A07P3S2DB		C3									7.3	2.0	1.5	2.0	1.5	2.0
CFW500A10P0S2DB		C3									10	3.0	2.2	3.0	2.2	3.0
CFW500A01P6B2DB		Blank									1.6	0.25	0.18	0.33	0.25	0.33
CFW500A02P6B2DB		Blank	2.6	0.5	0.37	0.75	0.55	0.75								
CFW500A04P3B2DB		Blank	4.3	1.0	0.75	1.5	1.5	1.5								
CFW500A07P3B2DB		Blank	7.3	2.0	1.5	2.0	1.5	2.0								
CFW500A10P0B2DB		Blank	10	3.0	2.2	3.0	2.2	3.0								
CFW500A16P0T2DB		Blank	16	5.0	3.7	5.5	4.0	5.5								
CFW500B24P0T2DB		Blank	B	24	7.5	5.5	7.5	5.5		7.5						
CFW500B28P0T2DB		Blank or C3		28	10	7.5	10	7.5		10						
CFW500B33P0T2DB		Blank or C3		33	12.5	9.2	12.5	9.2		12.5						

Notes: 1) The power values for maximum applicable motor shown in the tables above are reference values and valid for WEG motors. IEC motor powers are based on motor WEG four-pole W22 High Efficiency IE2 three-phase induction motors with power supply of 220 V, 230 V, 380, 400 V, 525 or 575 V. NEMA motor power are based on WEG four pole W22 Premium. Motor rated currents may vary with speed and manufacturer, therefore, use the motor power ratings above only as a guidance. The proper sizing of the CFW500 to be used must be determined as a function of the rated current of the motor used.
 2) The rated current informed for models of frames A and B are for HD (heavy duty) operation.



Specification

CFW500 IP66 (NEMA Type 4x) - 380-480 V



CFW500 variable speed drive											Maximum applicable motor ¹⁾					
Reference ²⁾								Power supply (V)		Frame size	Rated current (A) ²⁾	IEC				UL
												60 Hz		50 Hz		60 Hz
Coding (available options for each model)												380 V ac		380-400 V ac	400 V ac	440-460 V ac
												HP	KW	HP	KW	HP
1, 2, 3, 4, 5 and 6	7	8	9	10	11.1	11.2	12									
CFW500A01P0T4DB	66	Blank or C3	Blank or DS	Blank	Blank or H00	Blank or EC	Blank or Sxx	Three-phase	380-480	A	1.0	0.25	0.18	0.5	0.37	0.5
CFW500A01P6T4DB											1.6	0.5	0.37	0.75	0.55	0.75
CFW500A02P6T4DB											2.6	1.5	1.1	1.5	1.1	1.5
CFW500A04P3T4DB											4.3	2.0	1.5	2.0	1.5	3.0
CFW500A06P1T4DB											6.1	3.0	2.2	4.0	3.0	4.0
CFW500BA02P6T4DB											2.6	1.5	1.1	1.5	1.1	1.5
CFW500A04P3T4DB											4.3	2.0	1.5	2.0	1.5	2.0
CFW500A06P5T4DB											6.5	3.0	2.2	4.0	3.0	5.0
CFW500A10P0T4DB											10	5.0	3.7	5.5	4.0	7.5
CFW500B14P0T4DB											14	7.5	5.5	7.5	5.5	10
CFW500B16P0T4DB											16	10	7.5	10	7.5	10
CFW500B24P0T4DB											24	15	11	15	11	15
CFW500B31P0T4DB											31	20	15	20	15	25

CFW500 IP66 (NEMA Type 4x) - 500-600 V

CFW500 variable speed drive											Maximum applicable motor ¹⁾						
Reference ²⁾								Power supply (V)		Frame size	Rated current (A) ²⁾	IEC				UL	
												60 Hz		50 Hz		50 Hz	60 Hz
Coding (available options for each model)												575 V ac		575 V ac	525 V ac	575 V ac	
												HP	KW	HP	KW	KW	HP
1, 2, 3, 4, 5 and 6	7	8	9	10	11.1	11.2	12										
CFW500B01P7T5DB	66	Blank	Blank or DS	Blank	Blank or H00	Blank or EC	Blank or Sxx	Three-phase	600	B	1.7	1.0	0.75	1.0	0.75	0.75	1.5
CFW500B03P0T5DB											3.0	2.0	1.5	2.0	1.5	1.5	2.0
CFW500B04P3T5DB											4.3	3.0	2.2	3.0	2.2	2.2	3.0
CFW500B07P0T5DB											7.0	5.0	3.7	5.5	4.0	4.0	5.0
CFW500B10P0T5DB											10	7.5	5.5	7.5	5.5	5.5	10
CFW500B12P0T5DB											12	10	7.5	10	7.5	7.5	10

Notes: 1) The power values for maximum applicable motor shown in the tables above are reference values and valid for WEG motors. IEC motor powers are based on motor WEG four-pole W22 High Efficiency IE2 three-phase induction motors with power supply of 220 V, 230 V, 380, 400 V, 525 or 575 V. NEMA motor power are based on WEG four pole W22 Premium. Motor rated currents may vary with speed and manufacturer, therefore, use the motor power ratings above only as a guidance. The proper sizing of the CFW500 to be used must be determined as a function of the rated current of the motor used.
 2) The rated current informed for models of frames A and B are for HD (heavy duty) operation.

Specification

Optional Items

These are hardware resources added to the CFW500 in the manufacturing process, and they should be requested via smart code.

Internal Dynamic Braking (IGBT)

Used for quick stop of the motor with external¹⁾ braking resistor.

The braking IGBT is available as standard for the whole line, except for frame A of IP20 version.

Note: 1) External braking resistor not included. To specify the correct braking resistor, please refer to the CFW500 User's Manual.

NEMA1 Protection Kit³⁾ (N1)

Insert “.N1” in item 7 of the smart code frame sizes A, B, C, D, E or F.

According to the National Electrical Manufacturers Association (NEMA) standard, Type 1.

- Protects²⁾ against penetration of foreign solid objects (falling dust)
- Prevents access to hazardous parts
- Can also be acquired as an accessory (see accessories)

Notes: 2) Not recommended for external use, only indoor applications or inside enclosures.

3) Image of frame size A with NEMA1 kit.



3)

Disconnect Switch⁴⁾

Built-in disconnect switch for in the product for easy and safe maintenance or switching the mains off.

Note: 4) Only available for models with IP66 protection degree.



Internal RFI Filter

Inverters with internal RFI filter (code C2 or C3) when installed, maintained and used on the application they were designed for, and in compliance with the relevant installation standards and manufacturer's instructions, reduce conducted disturbance from the inverter to the main power supply in high frequency band (>150 kHz), complying to the relevant EMC standards, such as EN 61800-3 and EN 55011.

Conformal Coating

The standard version of the CFW500 offers protection class 3C2 - according to IEC 60721-3-3, ensuring greater protection for applications in environments with corrosive chemicals.

It is possible to request an extra coating on the internal circuit boards, protection class 3C3 - according to IEC 60721-3-3, by adding EC to item 11 of the smart code, ensuring even greater protection for applications in harsh corrosive environment.

Note: in order to select the CFW500 without plug-in module (H00) and with extra coating on the internal circuit boards (HEC), H00EC must be filled in item 11 of the smart code.



Pump Genius

To use CFW500 with the Pump Genius contact WEG Automation sales department.

Accessories

Plug-In Module

On the CFW500, it is possible leave to choose later the model of the internal plug-in module by entering H00 in item 11 of the smart code. In this case, it is necessary to select the plug-in module as an accessory, according to the table bellow.

In case H00 is not selected in item 11 of the smart code, the CFW500 will be supplied with the CFW500-IOS plug-in. You must always use one plug-in module per CFW500.

Reference	Description	Illustrative figures
	Input and output (I/O) expansion	
CFW500-IOS ¹⁾	Standard plug-in module (included in the version with plug-in module)	
CFW500-IOD	Digital input and output (I/O) expansion plug-in module	
CFW500-IOAD	Digital and analog input and output (I/O) expansion plug-in module	
CFW500-IOR-B	Relay output expansion plug-in module	
	Functionality expansion	
CFW500-ENC	Plug-in module with encoder input	
CFW500-CUSB	Plug-in module with USB port	
	Communication on Fieldbus network	
CFW500-CCAN	CAN communication plug-in module (CANopen/DeviceNet)	
CFW500-CRS232	RS232 communication plug-in module	
CFW500-CRS485-B	RS485 communication plug-in module	
CFW500-CPDP	Profibus-DP communication plug-in module	
CFW500-CETH-IP	EtherNet/IP communication plug-in module	
CFW500-CEMB-TCP	Modbus-TCP communication plug-in module	
CFW500-CEPN-IO	PROFINET IO communication plug-in module	
Reference	Description	Illustrative figures
	Memory	
CFW500-MMF	Flash memory module	
	Interfaces	
CFW500-HMIR	Remote operating interface (HMI)	
CFW500-CCHMIR1M	1-meter cable set for remote operating interface (HMI)	
CFW500-CCHMIR2M	2-meter cable set for remote operating interface (HMI)	
CFW500-CCHMIR3M	3-meter cable set for remote operating interface (HMI)	
CFW500-CCHMIR5M	5-meter cable set for remote operating interface (HMI)	
CFW500-CCHMIR75M	7.5-meter cable set for remote operating interface (HMI)	
CFW500-CCHMIR10M	10-meter cable set for remote operating interface (HMI)	
	Description	
CFW500-KN1A	NEMA 1 Kit - size A (standard for option N1)	
CFW500-KN1B	NEMA 1 Kit - size B (standard for option N1)	
CFW500-KN1C	NEMA 1 Kit - size C (standard for option N1)	
CFW500-KN1D	NEMA 1 Kit - size D (standard for option N1)	
CFW500-KN1E	NEMA 1 Kit - size E (standard for option N1)	
CFW500-KPCSA	Shielding kit for the power cables - size A (standard for option C2 and C3)	
CFW500-KPCSB	Shielding kit for the power cables - size B (standard for option C2 and C3)	
CFW500-KPCSC	Shielding kit for the power cables - size C (standard for option C2 and C3)	
CFW500-KPCSD	Shielding kit for the power cables - size D (standard for option C2 and C3)	
CFW500-KPCSE	Shielding kit for the power cables - size E (standard for option C2 and C3)	

Note: 1) Accessory already included if the CFW500 version with the standard plug-in module is selected.
The plug-in modules can also be sold separately as an accessory item or spare part.

Accessories

Configuration of the Plug-In Modules¹⁾

Plug-in module	Functions															
	Inputs		Outputs			USB port	Input for Encoder ³⁾	Fieldbus networks							Supply	
	Digital	Analog	Analog	Digital relay	Digital transistor			CANopen DeviceNet	RS232	RS485	Profibus-DP	EtherNet/IP	Modbus-TCP	PROFINET IO	10 V	24 V
CFW500-IOS	4	1	1	1	1	-	-	-	-	1	-	-	-	-	1	1
CFW500-IOD	8	1	1	1	4	-	-	-	-	1	-	-	-	-	1	1
CFW500-IOAD	6	3	2	1	3	-	-	-	-	1	-	-	-	-	1	1
CFW500-IOR-B	5 ²⁾	1	1	4	1	-	-	-	-	1	-	-	-	-	1	1
CFW500-ENC	5 ²⁾	1	1	4	1	-	1	-	-	1	-	-	-	-	1	1
CFW500-CUSB	4	1	1	1	1	1	-	-	-	1	-	-	-	-	1	1
CFW500-CCAN	2	1	1	1	1	-	-	1	-	1	-	-	-	-	1	-
CFW500-CRS232	2	1	1	1	1	-	-	-	1	1	-	-	-	-	-	1
CFW500-CRS485-B	4	2	1	2	1	-	-	-	-	2	-	-	-	-	1	1
CFW500-CPDP	2	1	1	1	1	-	-	-	-	1	1	-	-	-	-	1
CFW500-CETH-IP	2	1	1	1	1	-	-	-	-	1	-	1	-	-	-	1
CFW500-CEMB-TCP	2	1	1	1	1	-	-	-	-	1	-	-	1	-	-	1
CFW500-CEPN-IO	2	1	1	1	1	-	-	-	-	1	-	-	-	1	-	1

Note: 1) All plug-in models have at least one RS485 port. The CFW500-CRS485 plug-in module has two RS485 ports. The CFW500 allows the installation of one plug-in module per unit.

2) The digital input DI5 is always NPN, and it cannot be configured for PNP like the others.


3) Incremental Encoder (A/A - B/B).

See the installation guides of the plug-in modules on the website www.weg.net



Dimensions and Weights

IP20 Version



Size	A	B	C	D	H	L	P	Weight
	mm [in]	mm [in]	mm [in]	mm [in]	mm [in]	mm [in]	mm [in]	
A	50 [1.97]	175 [6.89]	11.9 [0.47]	7.2 [0.28]	189 [7.44]	75 [2.95]	150 [5.91]	0.8 [1.76]
B	75 [2.95]	185 [7.3]	11.8 [0.46]	7.3 [0.29]	199 [7.83]	100 [3.94]	160 [6.3]	1.2 [2.65]
C	100 [3.94]	195 [7.7]	16.7 [0.66]	5.8 [0.23]	210 [8.27]	135 [5.31]	165 [6.5]	2 [4.4]
D	125 [4.92]	290 [11.41]	27.5 [1.08]	10.2 [0.4]	306.6 [12.1]	180 [7.08]	166.5 [6.55]	4.3 [9.48]
E	150 [5.9]	330 [13]	34 [1.34]	10.6 [0.4]	350 [13.8]	220 [8.7]	191.5 [7.5]	10 [22.05]
F	200 [7.87]	525 [20.67]	42.5 [1.67]	15 [0.59]	550 [21.65]	300 [11.81]	254 [10]	26 [57.3]

Note: for the dimensions in the NEMA type 1 version, refer to the user manual.

IP66 Version




Size	A	B	C	D	E	H	L	P		Weight
	mm [in]	mm [in]	mm [in]	mm [in]	mm [in]	mm [in]	mm [in]	P1	P2	
								mm [in]	mm [in]	
A	150 [5,9]	250 [9,83]	5,7 [0,22]	7,5 [0,3]	225 [8,86]	265 [10,43]	165 [6,5]	227 [8,93]	252,5 [9,94]	10 [22,05]
B	200 [7,86]	325 [12,79]	5,7 [0,22]	7,5 [0,3]	300 [11,82]	340 [13,39]	215 [8,46]	227 [8,93]	252,9 [9,96]	12 [26,5]

Notes: P1 = Measure without disconnect switch.
P2 = Measure with disconnect switch.

Standards

Standards	Safety standards	UL 508C - Power conversion equipment
		UL 840 - Insulation coordination including clearances and creepage distances for electrical equipment
		EN 61800-5-1 - Safety requirements electrical, thermal and energy
		EN 50178 - Electronic equipment for use in power installations
		EN 60204-1 - Safety of machinery. Electrical equipment of machines. Part 1: general requirements Note: In order to have a machine in accordance with this standard, the manufacturer of the machine is responsible for installing an emergency stop device and a device for disconnection from the power line
		EN 60146 (IEC 146) - Semiconductor converters
		EN 61800-2 - Adjustable speed electrical power drive systems - Part 2: general requirements - Rating specifications for low voltage adjustable frequency AC power drive systems
	Electromagnetic compatibility standards	EN 61800-3 - Adjustable speed electrical power drive systems - Part 3: EMC product standard including specific test methods
		EN 55011 - Limits and methods of measurement of radio disturbance characteristics of industrial, scientific and medical (ISM) radio-frequency equipment
		CISPR 11 - Industrial, scientific and medical (ISM) radio-frequency equipment - Electromagnetic disturbance characteristics - Limits and methods of measurement
		EN 61000-4-2 - Electromagnetic compatibility (EMC) - Part 4: testing and measurement techniques - Section 2: electrostatic discharge immunity test
		EN 61000-4-3 - Electromagnetic compatibility - Part 4: testing and measurement techniques - Section 3: radiated, radio-frequency, electromagnetic field immunity test
		EN 61000-4-4 - Electromagnetic compatibility - Part 4: testing and measurement techniques - Section 4: electrical fast transient/burst immunity test
		EN 61000-4-5 - Electromagnetic compatibility - Part 4: testing and measurement techniques - Section 5: surge immunity test
		EN 61000-4-6 - Electromagnetic compatibility - Part 4: testing and measurement techniques - Section 6: immunity to conducted disturbances, induced by radio-frequency fields
	Mechanical construction standards	EN 60529 - Degrees of protection provided by enclosures (IP code)
		UL 50 - Enclosures for electrical equipment
		IEC60721-3-3 - Classification of environmental conditions - part 3: classification of groups of environmental parameters and their severities - Section 3: stationary use at weather protected locations level 3M4.



Technical Specifications


Power rating	Power supply	Tolerance: -15 to +10%
		Frequency: 50/60 Hz (48 Hz to 62 Hz)
		Phase imbalance: ≤3% of the rated phase-phase input voltage
		Transient voltages and overvoltages according to Category III (EN 61010/UL 508C)
		Maximum of 10 (line) connections per hour (1 every 6 minutes)
		Typical efficiency: ≥97%
Control	Method	V/F (scalar) VWV: voltage vector control Vector without encoder (sensorless) and closed loop vector with encoder PM VWV: voltage vector control for permanent magnet motors
	Output frequency	0 to 500 Hz, resolution of 0.015 Hz
Performance	V/F Control	Speed regulation: 1% of the rated speed (with slip compensation) Speed variation range: 1:20
	Vector control (VWV)	Speed regulation: 1% of the rated speed Speed variation range: 1:30
	Sensorless	Speed regulation: 0.5% of the rated speed Speed variation range: 1:100
	Vector control with Encoder	Speed regulation: 0.1% of the rated speed Speed variation range: 1:100
	PM VWV Control	Regulation: 0.1 % of the rated speed Speed variation range: 1:20
Environment conditions	Temperature around the CFW500	-10 °C to 40 °C - NEMA type 1 (sizes A to E) -10 °C to 40 °C - IP20 (sizes A to E) when installed by side and / or with RFI filter -10 °C to 50 °C - IP20 (sizes A to E) without RFI filter 0 °C to 40 °C - IP20 (size F) with or without RFI filter For sizes A to E, when operating temperatures are above the specification, it is necessary to apply 2% of current derating for each Celsius degree (°C), limited to an increase of 10 °C. For size F, when operating temperatures are above the specification, it is necessary to apply 1% of current derating for each Celsius degree (°C) up to 50 °C, and 2% up to 60 °C (maximum).
	Aggressive environments	Protection Class 3C2 - Standard coating on the internal circuits, according to IEC 60721-3-3 (standard model) Protection Class 3C3 - Extra coating - optional, according to IEC 60721-3-3 (optional)
	Air relative humidity	5% to 95% non-condensing
	Altitude	Up to 1,000 m (maximum altitude under normal conditions) 1,000 to 4,000 m: current derating of 1% for each 100 m above 1,000 m of altitude
	Pollution degree	2 (EN 50178 and UL 508C), with non-conductive pollution Condensation must not cause conduction of the accumulated residues
Inputs ¹⁾	Analog	1 isolated input. Levels: (0 to 10) V or (0 to 20) mA or (4 to 20) mA Linearity error ≤0.25% Impedance: 100 kΩ for voltage input, 500 Ω for current input Programmable functions, including PTC input Maximum voltage accepted in the inputs: 30 V dc
	Digital	4 isolated inputs Programmable functions: Active high (PNP): maximum low level of 15 V dc; minimum high level of 20 V dc Active low (NPN): maximum low level of 5 V dc; minimum high level of 9 V dc Maximum input voltage of 30 V dc Input current: 4.5 mA Maximum input current: 5.5 mA
Outputs ¹⁾	Analog	1 isolated output. Levels (0 to 10) V or (0 to 20) mA or (4 to 20) mA Linearity error ≤0.25% Programmable functions RL ≥10 kΩ (0 to 10 V) or RL ≤500 Ω (0 to 20 mA / 4 to 20 mA)
	Relay	1 relay with NO/NC contact Maximum voltage: 240 V ac Maximum current of 0.5 A Programmable functions
	Transistor	1 isolated open sink digital output (using as reference the 24 V dc power supply) Maximum current of 150 mA (maximum capacity of the 24 V dc power supply) ²⁾ Programmable functions
	Power supply	24 V dc power supply. Maximum capacity: 150 mA ²⁾ Power supply of 10 V dc. Maximum capacity: 2 mA
Communication	Selectable plug-in	Fieldbus: Modbus-RTU, CANopen, DeviceNet, Profibus-DP, EtherNet/IP, Modbus-TCP, PROFINET IO USB, RS485 and RS232 ports
Safety	Protection	Phase-phase overcurrent/short circuit in the output Phase-ground overcurrent/short circuit in the output Undervoltage/overvoltage in the power Overtemperature of the heatsink Motor overload Overload on the power module (IGBTs) External fault / alarm Programming error
Operating interface (HMI)	Standard (built in the CFW500)	9 keys: Run/Stop, Increment, Decrement, Direction of rotation, Jog, Local/Remote, Back/Esc and Enter/Menu LCD Display It allows accessing/changing all the parameters Accuracy of the indications: Current: 5% of the rated current Speed resolution: 0.1 Hz
Protection degree	IP20	Sizes A, B, C, D, E and F
	NEMA1/IP20	Sizes A, B, C, D, E and F with NEMA1 kit
	IP66	Sizes A and B (from 1.0 A to 31 A)

Notes: 1) The number and/or types of analog/digital inputs/outputs may vary according to the plug-in module (accessory) used. In the table above, the standard plug-in module (CFW500-IOS) was taken into account. For further information, refer to the CFW500 user manual.

2) The maximum capacity of 150 mA considers the load of the 24 V power supply plus the transistor output, that is, the sum of the consumption of both must not exceed 150 mA.

3) Designed for exclusive industrial or professional use.

Block Diagram of IP20 or NEMA Type 1 Version




Notes: 1) The number of inputs and outputs (analog and digital), as well as other resources, may vary according to the plug-in module used. For further information, refer to the CFW500 user manual.

2) Not available for size A.

3) Connection available for sizes D and E only. Inductor on the DC link not included. Sizes F has DC link inductor built-in as standard, to protect the drive against current spikes.

4) Resistor not included. Internal dynamic braking (IGBT) built-in the whole line, except for frame size A of IP20 version.

Block Diagram of IP66 / NEMA Type 4x Version



Notes: 1) The number of inputs and outputs (analog and digital), as well as other resources, may vary according to the plug-in module used. For further information, refer to the CFW500 user manual.
 2) Resistor not included. Internal dynamic braking (IGBT) built-in in the whole CFW500 IP66 version.



Global presence is essential, as much as understanding your needs.

Global Presence

With more than 30.000 employees worldwide, WEG is one of the largest electric motors, electronic equipments and systems manufacturers. We are constantly expanding our portfolio of products and services with expertise and market knowledge. We create integrated and customized solutions ranging from innovative products to complete after-sales service.

WEG's know-how guarantees our **CFW500** are the right choice for your application and business, assuring safety, efficiency and reliability.



Availability is to have a global support network



Partnership is to create solutions that suit your needs



Competitive edge is to unite technology and innovation



Know More



High performance and reliable products to improve your production process.



Excellence is to provide a whole solution in industrial automation that improves our customers productivity.

Visit: www.weg.net

 youtube.com/wegvideos

For WEG's worldwide
operations visit our website



www.weg.net



AUTOMATION

 +55 47 3276.4000

 automacao@weg.net

 Jaraguá do Sul - SC - Brazil

Cod: 50036259 | Rev: 13 | Date (m/a): 06/2020.

The values shown are subject to change without prior notice.

The information contained is reference values.